

4.054HT-4.063HT High-Temperature Combined Bearings

Series identification sheet. HT capability depends on the quoted grease, seals and execution.

Model	Execution	Verification
4.054HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.055HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.056HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.057HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.058HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.059HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.060HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.061HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.062HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature
4.063HT	High-temperature execution	Confirm base dimensions, grease, seals and rated temperature

Verification notes

- Published family range: 4.054HT-4.063HT.
- Do not infer temperature capability from the base model alone.

Before ordering, confirm the current controlled drawing, suffix, mounting geometry, load case, lubrication, temperature and inspection scope.