

MR.961-MR.968 Screw-Adjustable Combined Bearings

Complete factory catalog geometry and ratings. Axial adjustment uses a UNI 5929 / DIN 916 screw.

Geometry

Model	d	D	C	H min	H max	H1 min	H1 max	H2	D1	C1	D2	d1	Angle	r	R	R1	V	V1	Screw
MR.961	30	62	20	37.5	39.5	30.5	32.5	7	50	-	Dia 26	42	20	3	500	500	2.5	-	M10
MR.962	35	70.1	23	38.5	40.5	31.5	33.5	7	57	-	Dia 30	48	20	3	500	500	3	M6x1	M10
MR.963	40	77.7	23	40.7	42.7	31.7	33.7	9	61	-	Dia 30	54	20	3	700	700	4	M6x1	M10
MR.964	45	88.9	30	48.5	51	36.5	39	12	68	21	Dia 33	59	20	4	700	700	4	M6x1	M10
MR.965	50	101.9	28	46	48.5	33	35.5	13	77	21	Dia 33	67	20	4	850	700	2.5	M6x1	M10
MR.966	55	107.7	31	53.5	56.5	41.5	44.5	12	82	30	Dia 42	71	20	4	1000	700	6	M6x1	M16
MR.967	60	123	33	61.5	64.5	49.5	52	12	94	30	Dia 42	78	15	4	1000	1000	6.5	M6x1	M16
MR.968	60	149	43	75.5	79	58.5	62	17	116	45	Dia 63	103	15	4	1000	1000	6.8	M6x1	M10

Load ratings, speed and mass

Model	Cr kN	C0r kN	Ca kN	C0a kN	Speed rpm	Mass kg
MR.961	39	65	-	-	900	0.52
MR.962	56	93	-	-	900	0.60
MR.963	58	101.5	-	-	800	0.82
MR.964	84	133	15	22	700	1.43
MR.965	91	153	18	22	700	1.70
MR.966	94	162	31	40	650	2.45
MR.967	132	242	31	40	500	3.50
MR.968	179	353	68	71	400	6.50

Verification notes

- DIN 620 P0 tolerance and clearance basis.

- ISO 76 and ISO 281 load-rating basis.

Confirm the current controlled drawing, suffix, mounting geometry, load case, lubrication, temperature and inspection scope before ordering.